

SnapGear SOHO+



"Rated 4 stars"

-- Australian PC User Magazine

"That SOHO+ absolutely rocks btw, easy to setup ... It's very fast, reliable, only takes 10 seconds to reboot if necessary. All in all a superior product."

The SnapGear SOHO+ is a 2-port broadband VPN Firewall Appliance with two serial ports for narrowband fallback or for setting up for dial-in access.

MSRP US\$299 (USA price only) Available world-wide.

N E W! Buy a SOHO+ and be entitled to a complimentary one year URL Content Filtering license (Picket 5 User) on us.

- Buy online
- Find nearest reseller
- Reviews
- View Datasheet (PDF)
- Compare overview of product family
- Compare detailed features with other models
- Compare against our competitors
- SnapGear Online Emulator

Features

- Full IPSec VPN (Virtual Private Network) Capability
- Full PPTP VPN client and server
- Up to 10Mbps LAN throughput
- No per-user licensing or restrictions
- Web console
- Highly interoperable with other leading brands
- No third-party client software required
- Can handle more simultaneous tunnels than the SnapGear LITE/LITE+

Recommended for:

- Medium businesses needing to support multiple office-office connections and telecommuter VPN access
- Suitable for routing ADSL and Cable up to T1, DS1 and E1
- Suitable for VPN up to 1-2Mbps (most Cable, ADSL, and T1)

Specifications

- VPN - IPSec
 - Peer-to-peer (initiate and terminate)
 - ESP and AH payloads
 - Supports aggressive mode
 - Dead peer detection
 - Compression (deflate / gzip type algorithm)
 - DES 56-bit, 3DES 168-bit, AES 256-bit encryption
 - Hashes HMAC - MD5 and SHA-1 authentication
 - IKE/ISAKMP Diffie-Hellman key exchange
 - Diffie-Hellman Groups (1,2,5) and Oakley Groups (14,15,16) to 4096-bits
 - X.509 certificates DER, PEM formats
 - Pre-shared secrets
 - Dynamic IP address end-points
 - Dynamic DNS IPSec support
 - Authentication up to 2048-bit for RSA key signatures
 - Multiple subnets
 - NAT traversal
 - Up to 100 IPSec tunnels
 - Up to 1 Mbps IPSec 3DES throughput
 - Up to 2 Mbps IPSec AES 128-bit throughput
 - Up to 2 Mbps IPSec AES 196-bit throughput
 - Up to 2 Mbps IPSec AES 256-bit throughput
- VPN - L2TP
 - IPSec config Wizard
 - L2TP over IPSec
 - Autonomous L2TP
 - Client: NAT, default route via L2TP
 - Server: specify client IP address range
- VPN - PPTP
 - v2 client and server
 - Pass-through mode also
 - MPPE 40 to 128-bit RC4 encryption
 - PAP/CHAP/MS CHAPv2 authentication
 - L2TP & GRE tunneling extensions
 - Up to 10 PPTP client tunnels
 - Up to 20 PPTP server tunnels
 - Up to 2 Mbps RC4 throughput
- Stateful firewall
- Routing
- DHCP - client and server
- PPPoE (for ADSL support)
- NAT - static and dynamic
- NAT/PAT - port forwarding
- Connection sharing
- Anti-intrusion
- Logging (local and remote)
- Traffic shaping (QoS)
- IP aliases
- NTP client and server
- Free firmware updates - downloadable via Internet
- Web management
- CLI (Telnet) management
- Initial setup via either static IP address or dynamic IP address (DHCP client)
- Bridging (802.1d)
- Administration user accounts
- RADIUS / TACACS+
- DNS enhanced caching, masquerading, proxy, multiple DNS server proxying
- RAS (dial-in)
- Fail-over / high availability
- Dial on demand
- 10 Mbps routed throughput
- 10 Mbps PPPoE throughput
- Status LEDs
- WAN port - 1x10BaseT
- LAN port - 1x10BaseT
- Serial ports - 2 (dial-in, or dial-on-demand)
- Memory - 2Mb Flash, 16Mb RAM
- Power - 5V 1.5A
- Weight - 1lb (500g)
- Dimensions - 10"x6"x1.5" (250mmx160mmx40mm)
- Operating temperature 0C to 40C
- Storage temperature -20C to 70C
- Humidity 0 to 95%, non-condensing
- Certification - office
- Warranty - 1 year*, optional Extended Four Year Warranty

*Except where required to be 2 years by law

SnapGear Inc.
7984 South Welby Park Drive, Suite #101
Salt Lake City UT 84088
USA
Phone 801-282-8492
Fax 801-282-8496
E-mail contact@snapgear.com